

MATERIAL SAFETY DATA SHEET

PRODUCT AND COMPANY IDENTIFICATION

Product Name: Ethylene Propylene Diene Monomer (EPDM) Rubber 'Final'

Product No.: E-093

1

Manufacturer Name:

Okin Huasu Rubber and Plastics Group Limited

A-1002, Yihe International Mansion,

No. 10 Hongkong Middle Road, Qingdao, China.

Office:+86-532-5556 5558 Fax: +86-532-86662018

Intended Use: EPDM Rubber

HAZARDS IDENTIFICATION

Emergency Overview

Physical State: Solid EPDM rubber

Color: Black

2

Odor: No data available.

ATTENTION:

Possible cancer hazard-may cause cancer based on animal data. Rubber compounds generally do not pose a health hazard unless heated. Under normal conditions of processing and use, exposure to the chemical constituents in this product is unlikely. All ingredients are tightly bound in a polymeric matrix that has a negligible vapor pressure so there is a low potential for inhalation or ingestion of ingredients. Skin(dermal) contact is possible

Potential Health Effects

Inhalation: Grinding and sanding this product may generate dust. Dust may irritate throat



and respiratory system and cause coughing. Lower concentrations of fumes from burning this material may cause respiratory irritation with coughing, difficult in breathing, or shortness of breath. High concentrations may cause sever irritation, pulmonary edema(body fluid in the lungs) with coughing, wheezing, and effects, and collapse. Symptom may be delayed and progressively worsen.

Eye Contact: Grinding and sanding this product may generate dust. Dust may irritate the eyes. Decomposition products may cause eye irritation. Contact with hot material can cause thermal burns which may result in permanent damage.

Skin Contact: Prolonged or repeated skin contact

may cause irritation. Individuals sensitive

to small amounts of curing agents present may develop a rash(dermatitis). Contact with hot material can cause thermal burns which may result in permanent damage.

Ingestion: No adverse effects due to ingestion are expected.

Chronic Health Effects: Possible human cancer hazard. Carbon black has cancer in experimental animals. These ingredients are bound within the rubber and release is not expected.

Potential Physical / Chemical Effects: This product is not flammable.

OSHA Regulatory Status: When used for its intended purpose, this material is classified as hazardous in accordance with OSHA 29CFR 1910.1200.

Environment: The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Concentration*
Carbon black	1333-86-4	<31%
Ethylene-ethy1idenenorbomene-propylene	25038-36-2	<26%
terpolymer		
Ethylene-propylene copolymer	9010-79-1	<26%
Polyalky1benzene	None	<6%
Zinc oxide	1314-13-2	<3%
1,2-Polybutadiene	9003-17-2	<2%



Modified clay	66402-68-4	<2%
1H-Pyrrole-2,5- dione,1,1'-(1,3-phenylene)bis-	3006-93-7	<1.5%
Peroxide,[1,3(or1,4)-pheny1enebis(1-	25155-25-3	<1.5%
methy1ethylidene)]bis[1,1-dimethylethy1]		
		- , 0

^{*}All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. This chemical is hazardous according to OSHA/WHMIS criteria.

4 FIRST AID MEASURES

General: For contact with hot polymer: Flush eyes with lukewarm water for at least 15 minutes. Immerse skin in cool water. DO NOT attempt to remove polymer from skin as this can cause further damage. Get immediate medical attention is required if decomposition products are inhaled.

Inhalation: If fumes from heated product are inhaled: Move into fresh air and keep at rest. Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Consult a physician for specific advice.

Eye Contact: Dust in the eyes: Flush eyes thoroughly with water, taking care to rinse under eyelids. If irritation persists, continue flushing for 15 minutes, rinsing from time to time under eyelids. If discomfort continues, consult a physician.

Skin Contact: Remove contaminated clothing immediately and wash skin with soap and water. If irritation occurs, get medical assistance.

Ingestion: Rinse mouth thoroughly. Drink plenty of water. Get medical attention if symptoms occur.

5 FIRE-FIGHTING MEASURES

Extinguishing Media: This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable Extinguishing Media: Not applicable.

Special Fire Fighting Procedures: Use standard firefighting procedures and consider the



hazards of other involved materials.

Unusual Fire & Explosion Hazards: The product is non-combustible. If heated, toxic vapors may be formed. Burning this material, or exposing it to temperatures above 300° C may result in the release of irritating fumes.

Hazardous Combustion Products: Alcohols, Carbon Dioxide, Carbon Monoxide, Hydrocarbons.

Protective Measures: Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid prolonged or repeated contact with skin. Wear necessary protective equipment. See Section 8 of the MSDS for Personal Protective Equipment.

Spill Cleanup Methods: Shovel up and place in a container for salvage or disposal. For waste disposal, see section 13 of the MSDS.

Environmental Precautions: No specific precautions.

7 HANDLING AND STORAGE

Handling: All handling to take place in well-ventilated area. Avoid inhalation of dust and contact with skin and eyes. Wear protective gloves and appropriate clothing to prevent skin contact. Do not breathe fumes produced at elevated temperatures. Periodically clean work and storage to prevent dust accumulation. Observe good industrial hygiene practices.

Storage: Store in a cool, dry place out of direct sunlight. Keep containers tightly closed to prevent moisture absorption and contamination.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

•				
Chemical Name	Source	Туре	Exposure Limits	Notes
Carbon black	ACGIH	TWA	3.5 mg/m^3	·



Carbon black	NIOSH Guide	Concentration	1750 mg/m ³
Carbon black	black US.OSHA Table Z-		3.5 mg/m^3
	1		
Zinc oxide	ACGIH	STEL	10 mg/m ³
(Respirable fraction.)			
Zinc oxide	ACGIH	TWA	2 mg/m ³
(Respirable fraction.)			
Zinc oxide	NIOSH Guide	Concentration	500 mg/m ³
Zinc oxide	OSHA Z3	TWA	15Mppcf
(Respirable fraction.)			5mg/m ³
Zinc oxide (Total dust.)	OSHA Z3	TWA	50Mppcf
			15mg/m ³
Zinc oxide (Fume)	US.OSHA Table Z-	TWA	5 mg/m ³
	1		
Zinc oxide	US.OSHA Table Z-	TWA	5 mg/m ³
(Respirable fraction.)	1		

Engineering Controls: Provide adequate ventilation. If dust or fumes are generated during use, use local exhaust in combination with general ventilation as necessary to remove fumes/dust from the workers' breathing zone and to ensure exposures do not exceed applicable limits.

Respiratory Protection: No protection is ordinarily required under normal conditions of use and with adequate ventilation. During dust-raising work or inhalation of hot/molten material: Use a NIOSH-approved respirator (See 29 CRF 1910.134, respiratory protection standard).

Eye Protection: If contact with hot material may occur, safety glasses and face shield are recommended.

Hand Protection: Gloves are recommended for prolonged use. When material is heated, wear gloves to [protect against thermal burns.

Skin Protection: It is a good industrial hygiene practice to minimize skin contact. Thermally protective, chemical resistant apron and long sleeves are recommended when volume of hot material is significant.

Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.



PHYSICAL AND CHEMICAL PROPERTIES

Color: Black

9

Odor: No data available.

Odor Threshold: No data available.

Physical State: Solid rubber

PH: Not applicable

Melting Point: No data available. Freezing Point: No data available. Boiling Point: Not applicable.

Flash Point: Not applicable.

Evaporation Rate: Not applicable.

Flammability (Solid): No data available.

Flammability Limit-Upper(%): Not applicable. Flammability Limit-Lower(%): Not applicable.

Vapor Pressure: Not applicable.

Vapor Density (Air=1): Not applicable.

Specific Gravity: No data available.

Solubility in Water: insoluble

Solubility(Other): Not applicable.

Partition Coefficient(n-Octanol/water): Not applicable.

Autoignition Temperature: Not applicable.

Decomposition Temperature: No data available.

Explosive Properties: No data available.

10 STABILITY AND REACTIVITY

Stability: Stable under normal temperature conditions and recommended use.

Conditions to Avoid: Oxidizing agents

Incompatible Materials: In general, elastomers are incompatible with: Strong oxidizing agents. Reducing agents.

Hazardous Decomposition Products:

At Elevated Temperatures: Alcohols, Carbon Dioxide, Carbon Monoxide,



Hydrocarbons

Possibility of Hazardous Reactions: Will not occur. The product is fully polymerized.

11	TOXICOLOGICAL INFORMATION

Specified Substance(s)

Acute Toxicity:

Component Chemical Name	Test Results
1H-Pyrrole-2,5-dione,1,1'-(1,3-	Inhalation LC50(4HOUR(S), Rat): 55mg/m ³
phenylene)bis-	
1H-Pyrrole-2,5-dione,1,1'-(1,3-	Oral LD 50 (Rat): 1370mg/kg
phenylene)bis-	
Carbon black	Dermal LD50(Rabbit): >3000mg/kg
Carbon black	Oral LD50(Rat):>15400 mg/kg
Peroxide, [1,3(or 1,4)-pheny1enebis(1-me)]	Oral LD50(Rat):23000mg/kg

Listed Carcinogens: The rubber industry is listed as an exposure circumstance that is known to be carcinogenic to humans(Group 1). Carbon black: Certain carbon blacks have proved carcinogenic in animal studies. Inhalation animal studies of high concentrations resulted in chronic inflammation, lung fibrosis and lung tumors. Epidemiology studies of workers include findings of bronchitis, pneumonia, emphysema and excess cancer. Substances bound in a polymer or other matrix should present little or no hazard.

Chemical Name	IARC	NTP	OSHA	ACGIH
Carbon black	2B	Not Listed	Not Listed	Not Listed

IARC: 1=Carcinogenic to Humans; 2A=Probably Carcinogenic to Humans; 2B=Possibly Carcinogenic to Humans. Not listed= Either Group 3 (Not classifiable as to carcinogenicity to humans), Group 4 (Probably not carcinogenic to humans), or not evaluated by IARC.

Product Information

Other Acute: The principal components used in this product have been reacted and are no longer present in their original form. The finished polymerized product is an insert polyacrylic rubber, and exposure to the original constituents would not be expected under normal conditions. Like most high-molecular weight polymers, this product is not known to exhibit any adverse acute or chronic health effects. Burning this material or exposing it to temperatures in excess of 33 $^{\circ}$ C can generate irritating and toxic fumes. The type of compounds generated depends upon temperature and conditions. Health effects from these fumes can range from transient to severe eye, skin, and respiratory irritation, pulmonary edema, headache, nausea, drowsiness as well as a variety of other effects. Grinding and



sanding this product may generate dust. Dusts may irritate the lungs. Dust inhalation can also inhibit the clearance of toxic particles from the lung by decreasing the mobility of alveolar macrophages.

Chronic Toxicity: Possible cancer hazard - may cause cancer based on animal data.

12 ECOLOGICAL INFORMATION

Ecotoxicity: The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Specified Substance(s):

Chemical Name	Test
Carbon black	EC50(24hour(s), Daphnia
	magna): >5600mg/l
Carbon black	EC50(72hour(s), Green Alga): >10000mg/l
Carbon black	LC90(96hour(s), Zebra Fish): >10000mg/l

Mobility: The product is non-volatile. The product is insoluble in water.

Persistence and Degradability: No data available

Bioaccumulation Potential: No data available on bioaccumulation.

13 DISPOSAL CONSIDERATIONS

General Information: Dispose of waste and residues in accordance with local authority requirements.

Disposal Method: No specific disposal method required.

Container: Since emptied containers retain product residue, follow label warnings even after container is emptied.

14 TRANSPORT INFORMATION

DOT Not regulated



TDG Not regulated
<u>IATA</u> Not regulated
IMDG Not regulated
15 REGULATORY INFORMATION
Canadian Controlled Products Regulations: This product has been classified according to the
hazard criteria of the Canadian Controlled Products Regulations, Section 33, and the MSDS
contains all required information.
WHMIS Classification: D2A
Mexican Dangerous Statement: This is a Mexican "dangerous" product.
Inventory Status: All ingredients are either listed or exempt from listing on EINCS, DSL, or TSCA.
<u>US Regulations</u>
CERCLA Hazardous Substance List (40CFR 302.4): None
SARA Title III
Section 302 Extremely Hazardous Substances (40 CFR 355, Appendix A): None
Section 311/312(40 CFR 370)
\square Acute(Immediate) \square Chronic(Delayed) \square Fire \square Reactive \square Pressure Generating
Section 313 Toxic Release Inventory(40 CFR 372)

Chemical Name	CAS-No.	Concentration
Zinc oxide	1314-13-2	<3%

Clean Air Act(CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): None

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3): None



Drug Enforcement Act: None

TSCA: No component is listed on TSCA Sections 4(a), 5(a)(2),5(e)or12(b).

State Regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986(Proposition 65): Carbon black

Massachusetts Right-To-Know List: Carbon black; Zinc oxide

Michigan Critical Materials List (Michigan Natural Resources and Environmental Protection

Act(Act.451 of 1994)): None

Minnesota Hazardous Substances List: Carbon black; Zinc oxide

New Jersey Right-To-Know List: Carbon black; Peroxide, [1,3(or1,4)-phenylene bis(1-methylethy1idene)] bis[(1,1-dimethylethy1); Zinc oxide]

Pennsylvania Right-To-Know List: Carbon black; Zinc oxide **Rhode Island Right-To-Know List:** Carbon black; Zinc oxide

16 OTHER INFORMATION

HAZARD RATINGS

	Health Hazard	Fire Hazard	Reactivity Hazard	Special Hazard
NFPA	1	1	0	

	Health Hazard	Fire Hazard	Reactivity Hazard	Special Hazard
HMIS	1*	1	0	В

 $\hbox{0-Minimal; 1-Slight; 2-Moderate; 3-Serious; 4-Severe; *-Chronic Health Effect}$

B-Safety Glasses & Gloves

Issue Date: Sep. 12th 2012

Supercede Date: Sep. 16th 2012



SDS No.: 1003449

Disclaimer: The information provided on this data sheet was abstracted from supplier material safety data sheets and standard references in occupational health and toxicology. Federal-Mogul makes no representation or warranty with respect to the information obtained from such references. The information is however, as of the date provided, true and accurate to the best of Federal-Mogul's knowledge, and should be used to make an independent determination of the methods to safeguard workers and the environment.

OKIN HUASU RUBBER AND PLASTICS GROUP LIMITED



For and on behalf of OKIN HUASU RUSBER AND PLASTICS GROUP LIMITED 奥凯華塑橡塑集區有限文司